

Item	Piece	Product	Unit price EURO	Total price EURO
		<p>Drive axxent HSA smart – scheme A Automatic part-concealed lift & slide door hardware for HS elements with one sash in scheme A</p> <ul style="list-style-type: none"> • Automatic locking/release, lifting/lowering and movement of the HS sash • With intelligent micro-processor control, self-learning, closing forces according to the current regulations of the new DIN 18650 • With CB approval • Operation with SIEGENIA Comfort app* for smartphones or tablets • Motorised night vent • 10-minute automatic night ventilation • Selection of a limited opening width • Jam protection provided by current limiter incl. slow mode and stop in the area of the shear points • Smooth start and stop motion • Simple manual emergency operation in the event of a power failure • Wheelchair-accessible design and operation in accordance with DIN 18040 if used in conjunction with flat threshold • No restriction on entrance height • Simple connection via Euro plug or fixed connection • Suitable for max. sash weight of 400 kg incl. glass pane • Optionally with locking bolt or hook bolt gear • For RIB of 2,144 mm to 6,666 mm (with symmetrical split) and max. sash height up to 3,300 mm • Installation on the top frame with space of only approx. 45 mm required. The slide drive can be moved downwards depending on the profile system if space is at a premium. • Slide drive dimensions: 72 mm x 73 mm • Automatic teach-in due to reference run and position detection • 24 V power supply with Euro plug integrated into the slide drive • High level of functional reliability thanks to more than 25,000 tested switching cycles • Paint finish of the casing and caps possible in all RAL and NCS colours • Jigs available as accessories • Max. displacement force during operation: approx. 50 N (depending on sash weight and friction) • Traverse speed: approx. 150 mm/sec. • Operating time of lift drive: approx. 7 sec. • Supply voltage: 120–240 V AC, 48 W • Internal operating voltage: 24 V DC • Max. current consumption 0.2 A • Connection plug: Euro plug • Connecting clamp: for max. 2.5 mm² supply line • Cable type for cable routing by the customer in accordance with the specification: normally NYM (all-pole isolation required) • Protection class: IP 20 for dry locations • Working/ambient temperature: -5 to 50 °C • Compliance: CE symbol • Jam protection: electronic overload cut-off device / current limiter in accordance with standard • Produced in accordance with the relevant UVV and VDE regulations • Production certified in accordance with ISO 9001:2000 • It is possible to connect external devices such as key switches, access control systems, card readers, light barriers, etc. • Controlled by push button on the lift drive, by the SIEGENIA Comfort app* for smartphones or tablets or via an optional infrared remote control • Can be integrated into group controls or central domotics systems <p>Article set consisting of:</p> <ul style="list-style-type: none"> • 1 x concealed lift drive • 1 x surface-mounted slide drive incl. 24 V power supply • 1 x catches • 1 x emergency operating key • Fixing accessories (screws, cable holders) • Installation and operating instructions <p>Manufacturer: SIEGENIA-AUBI KG, drive type: DRIVE axxent HSA smart – scheme A Or equivalent: _____</p> <p>* The SIEGENIA Comfort app is compatible with iOS 8.0 or newer, iPhone, iPad and iPod touch, as well as with Android 5.0 or newer.</p>		