

Item	Piece	Product	Unit price EURO	Total price EURO
		<p>AEROTUBE AZ smart Wall-mounted ventilator with supply and exhaust air functions</p> <p>Suitable for installation in outside walls.</p> <p>Individual room ventilation unit for the ventilation and aerating of rooms with the following additional features:</p> <p>For wall thicknesses up to 500 mm.</p> <p>Air throughput exhaust air: Level 1 24 m³/h at L_{PA} = 26 dB (A) Level 2 43 m³/h at L_{PA} = 39 dB (A) Level 3 58 m³/h at L_{PA} = 46 dB (A)</p> <p>Inherent noise L_{PA} measured in accordance with DIN EN ISO 3745 (with room insulation 8 dB).</p> <p>Power consumption: max. 4.1 Watt Electrical connection: 230 Volt ~ Protection class: II; insulated; IP22</p> <p>Requirement-based ventilation with integrated temperature and humidity sensor for automatic control</p> <p>Fresh air operation with integrated G3 filter</p> <p>Discreet look, the functional unit is located in the pipe in the wall</p> <p>Indication that change of filter is required on the unit and in the SIEGENIA Comfort app</p> <p>When the front panel is removed for maintenance purposes, a safety switch cuts off the internal supply voltage.</p> <p>Control by button on the device or with SIEGENIA Comfort app* operation for smartphone or tablet</p> <p>Names, functions and assignments can be freely selected Cross ventilation can also be set via the SIEGENIA Comfort app*</p> <p>Technical approval (DIBt)</p> <p>Accessories Stainless steel weather grille hood PVC weather grille D160 Stainless steel weather grille Aluminium-zinc weather grille (choice of RAL)</p> <p>Product: SIEGENIA AEROTUBE AZ smart with electrical lock</p> <p>Delivery of device incl. accessories: _____ Assembly of the device: _____</p> <p>Product: SIEGENIA AEROTUBE WRG smart with manual lock</p> <p>Delivery of device incl. accessories: _____ Assembly of the device: _____</p> <p>* Notes on compatibility at www.siegenia.com/qr/comfort-app/faq</p>		

Vent duct EPP

The ducts are suitable for installation on the outside wall e. g. in WDVS systems.

Consisting of high-quality, expanded Polypropylene, it has a high resistance to chemicals and oils. Has a long service life (no corrosion) and is light-weight.

The manufacturing and fabrication of the foam particles is environmentally friendly and CFC-free.

High energy absorption and lightweight

Free from propellant gases and other chemical propellants

The ducts can be individually shortened by 250 mm lengthwise

Material: PVC EPP

Surface: black

Vent duct EPP, type FL

Consisting of vent duct and FL + cover

Dimensions of duct: 360 x 600 x 60 mm

Vent duct EPP, type SFL:

Consisting of vent duct SFL + transition piece + cover

Dimensions of duct: 360/360 x 780 x 60 mm

Selectable weather grille

Weather grille lamella

Consisting of: PVC weather grille, colour white (similar to RAL 9010 pure white), outlet duct, fixing set – depth-variable

Weather grille perforated grille

Consisting of: Aluminium weather grille, RAL colour choice, outlet duct, fixing set

Product: SIEGENIA **AEROTUBE with vent duct EPP TYPE FL**

Product: SIEGENIA **AEROTUBE with vent duct EPP TYPE FL**

Product: SIEGENIA **Weather grille lamella**

Product: SIEGENIA **Weather grille perforated grille**

Accessories

Extension for vent duct SFL – for extension between transition piece and corner drive with vent duct EPP, type SFL (dimensions: 360 x 250 mm)

Insulation plate 20 type FL

Depth 20 mm, WLG 040

Delivery and full installation