

Multi-point locks, key-operated MFS BSxxxx

Explanation of short texts

The standard short sales text for the multi-point locks consists of 39 characters and is structured as shown below:

Multi-point locks, key-operated MFS BSxxxx

Explanation of short texts

Position in short text:	1 - 3	4	5 - 10	11 - 12	13 - 14	15 - 16	17	18	19 - 20	21 - 22	23	24 - 25	26 - 27	28	29	30 - 31	32 - 33	34	35 - 37	38	39	40
	Assembly	Blank space	Item number	Latch type	Special function 1	Special function 2	Code for frame parts for multi-point lock with auxiliary box	Face plate contour	Height of profile plate	Face plate width	Face plate form	Backset in mm	PZ dimension in mm	Spindle square in mm	Stamp	DIN direction	Colour code	Type code size variant	Size variant	Code for main lock type	Recessed version of fastening holes	In standard = empty or S = special design
	MFS		BS2600	SA	--	T0	X	P	6-	24	K	45	92	8	-	LR	31	B	001	H	1	

MFS = multi-point lock, key operated

BS2100 = multi-point lock with comfort mushroom cam
 BS2200 = multi-point lock with H lock
 BS2300 = multi-point lock with round bolts
 BS2500 = multi-point lock with hook bolts
 BS2600 = multi-point lock with round bolt/hook bolt combination
 BS2800 = multi-point lock with roller bolt
 BS6000 = multi-point lock vertical locking with latch and deadbolt
 BS6600 = multi-point lock vertical locking with latch, deadbolt and round bolt/hook bolt combination

SA = soft lock latch 2 mm offset
 SL = soft lock latch bevelled
 FS = for fire rated doors
 PF = swing door roller latch
 FB = without latch, with guiding bolts for sliding doors
 OF = without latch

-- = without special function 1

-- = without special function 2
 T0 = including assembly routing "T0"
 T2 = including fitted safety lock "T2"
 OR = without deadbolt

Q = KfV frame parts usable with Q adjustment
 X = any desired KfV frame parts can be used
 - = no relevance

F = flat face plate
 P = U-profile face plate

xx = xx mm height of profile plate
 -- = 2 blank spaces with flat face plate

xx = xx mm secondary sash width

K = angular faceplate
 A = rounded faceplate

recess according to factory standard no. 1 = 1

85, 88, 92 and 94 mm PZ dimension = H
 72 and 74 mm PZ dimension = V

multi-point lock size variant

size variant type, B version

zinc-plated = 31
 zinc-plated and coated RAL 9016 white = V1
 zinc-plated and coated RAL 9007 = V3
 brushed matt stainless steel = 41

left side adjustment, suitable for right (standard) = LR
 right side adjustment, suitable for left side = RL
 suitable only for DIN left side = LS
 suitable only for DIN right side = RS
 no direction (e. g. with swing door roller latch) = OR

KfV stamp (standard) = -
 stamp SKG and KfV = M

Important: Positions in the text that are not required will be filled in with hyphens "-".

Hence the product features can always be found in the same position.

Please note: Features are not fully listed. Version EN - last revised: 2019-04-03

KFV

Ein Unternehmen der SIEGENIA GRUPPE